Software Engineering and Artificial Intelligence Systems

Volume: 02 Issue: 01 (2026)

www.seais.org/

Uncertainty-Regularized Neural Surrogates for Sparse Governing-Equation Identification from Observations

Andrew Sin[1], Natalie Yim[2]

[1] Division of AI, School of Data Science, Lingnan University, Hong Kong, Hong Kong SAR, China

[2] Department of Computer Science and Engineering, School of Engineering, Hong Kong University of Science and Technology, Hong Kong, Hong Kong SAR, China

Keyword: Sparse Identification, Neural Surrogates, Uncertainty Quantification, Governing Equations, Scientific Machine Learning

A B S T R A C T

The automated identification of governing equations from observational data has emerged as a transformative paradigm in scientific machine learning, enabling the discovery of complex physical laws without relying on first principles. However, contemporary sparse regression techniques frequently fail when applied to real-world datasets characterized by high levels of measurement noise and sparsity. To address these limitations, this paper introduces a novel framework utilizing uncertainty-regularized neural surrogates for the robust identification of nonlinear dynamics. By embedding probabilistic uncertainty quantification directly into the optimization objective of a neural surrogate model, the proposed method actively filters epistemic and aleatoric noise, yielding highly accurate derivative approximations. These refined spatial and temporal derivatives are subsequently passed to a sparse optimization module that identifies the minimal, most descriptive set of physical terms comprising the underlying partial differential equation. Extensive theoretical analysis and empirical evaluations across several chaotic and fluid dynamical systems demonstrate that the inclusion of an uncertainty-regularization term significantly mitigates the propagation of observational errors. The proposed framework maintains structural recovery accuracy even under severe noise perturbations that typically break deterministic models. This research provides a mathematically rigorous foundation for discovering parsimonious physical laws in highly uncertain operational environments.

INTRODUCTION

1.1 The Challenge of Data-Driven Scientific Discovery

The pursuit of understanding complex physical phenomena has traditionally relied on the formulation of mathematical models derived from empirical observation and established first principles. For centuries, scientists have translated observed behaviors in fluid mechanics, thermodynamics, and electromagnetism into governing partial differential equations. However, as contemporary scientific inquiry shifts toward increasingly complex, multi-scale systems where underlying fundamental laws remain obscure, the traditional paradigm faces significant bottlenecks. The advent of high-resolution sensor networks and advanced computational simulation has generated an unprecedented volume of observational data, catalyzing the development of data-driven methods for automated scientific discovery. The core objective of these methodologies is to infer the governing equations directly from measurement data, thereby bridging the gap between raw observation and interpretable physical theory. For a broader comparison, related research addresses evidence froma52-country panel analysis [1]. Despite the initial successes of early symbolic regression techniques, identifying the exact mathematical structure of a dynamical system from noisy, limited data remains profoundly challenging. Sparse regression frameworks have gained significant traction by framing the discovery process as a feature selection problem over a large library of candidate functional terms. The lasso introduces shrinkage with an L1 penalty, providing a standard sparse-estimation comparator for selecting candidate explanatory terms [2]. By applying sparsity-promoting regularization techniques, such approaches attempt to isolate the few relevant mathematical operators that dictate the evolution of the system. While theoretically elegant and highly effective on pristine synthetic datasets, these deterministic methods exhibit acute sensitivity to measurement noise and spatial-temporal resolution limits. The computation of numerical derivatives from raw, noisy observations inherently amplifies high-frequency noise, leading to completely spurious coefficient assignments and the subsequent failure of the sparse identification algorithm. For a broader comparison, related research addresses optimizing hybrid RIS-Aided ISAC systems in V2X networks: A deep reinforcement learning method for Anti-Eavesdropping techniques [3].

1.2 The Role of Uncertainty-Regularized Neural Surrogates

To mitigate the catastrophic impact of numerical differentiation on noisy data, researchers have increasingly turned to neural networks as differentiable surrogate models. By training a deep neural network to approximate the spatio-temporal state variables of the observed system, one can leverage automatic differentiation to obtain smooth, analytically exact derivative fields. However, standard neural surrogates often overfit the observational noise, effectively baking the measurement errors into the resulting derivative fields and completely undermining the subsequent equation identification phase. Standard regularization techniques such as weight decay and dropout provide only marginal improvements, as they do not explicitly account for the probabilistic nature of the measurement uncertainty. Qu and colleagues examine conditional denoising diffusion probabilistic model for point cloud upsampling [4]. This paper proposes a fundamental paradigm shift by introducing an uncertainty-regularized neural surrogate framework. Instead of merely fitting a deterministic function to the data, the proposed method estimates a probabilistic predictive distribution that captures both the inherent system noise and the uncertainty of the neural network parameters. By integrating an uncertainty-aware regularization term directly into the training objective, the network is penalized for confidently fitting noisy outliers. This regularized surrogate acts as an intelligent, physics-informed filter that produces highly robust derivative estimations. These enhanced derivatives are then utilized within a thresholded sparse regression algorithm to identify the true governing partial

differential equations. The overarching contribution of this work lies in systematically coupling Bayesian uncertainty quantification with sparse functional identification, thereby enabling the discovery of parsimonious physical laws under previously prohibitive noise conditions. A Bayesian treatment of latent representations is supplied by the QEP-LVM study [5]. In sparse equation discovery, uncertainty in an internal encoding could then be propagated into candidate coefficients, with any physical interpretation still checked against observed trajectories.

2. Background and Related Work

2.1 Sparse Identification of Nonlinear Dynamics

The identification of nonlinear dynamical systems has historically been approached through various system identification techniques, ranging from purely statistical autoregressive models to complex Volterra series expansions. The modern era of equation discovery was fundamentally transformed by the introduction of sparse identification methodologies, which leverage the assumption that most physical systems are governed by only a few key terms. The formulation involves constructing an extensive library of potential physical interactions, including polynomial expansions, trigonometric functions, and various spatial gradients. A sparse optimization algorithm, typically utilizing sequential thresholded least squares or absolute shrinkage and selection operator techniques, is then applied to find a minimal subset of these functions that accurately describes the temporal evolution of the system data. Xu and colleagues examine reinforced data-driven estimation for spectral properties of Koopman semigroup in stochastic dynamical systems [6].

While these methods have demonstrated remarkable capability in recovering equations like the Navier-Stokes and the Kuramoto-Sivashinsky equations from high-fidelity data, their reliance on accurate numerical differentiation constitutes a severe vulnerability. Traditional finite difference methods amplify high-frequency measurement noise by a factor proportional to the inverse of the grid spacing, rendering the constructed feature library virtually useless when applied to real-world sensor data. Various filtering and integral formulation techniques have been proposed to bypass direct differentiation, but they often require complex numerical integration schemes and domain-specific knowledge that limit their general applicability. Another relevant line of investigation concerns learning Koopman representations for complex dynamics with spectral residuals [7].

2.2 Neural Network Surrogates and Physics-Informed Frameworks

The rise of deep learning has introduced highly expressive, continuous function approximators capable of circumventing the limitations of discrete grid-based differentiation. A neural network can be trained to map spatio-temporal coordinates to the physical state variables of a system. Once trained, the network can be queried at any arbitrary point in space and time, and its derivatives with respect to the input coordinates can be computed exactly using backpropagation-based automatic differentiation. This approach inherently provides a smoothing effect, as the network acts as a low-pass filter over the scattered data points. The literature also considers on the role of discount factor in offline reinforcement learning [8].

Furthermore, the development of physics-informed machine learning has shown that neural networks can be constrained by physical laws to improve their generalization capabilities. In the context of equation discovery, however, the physics are precisely what we are trying to uncover, rendering traditional physics-informed loss functions inapplicable during the initial surrogate training phase. Consequently, researchers have attempted to jointly optimize the neural surrogate and the sparse coefficients of the governing equation. Yao and colleagues examine physics-Informed neural networks architecture for implicit governing physics with interpretability [9].




Figure 1Architectural Overview of the Uncertainty

Despite these advancements, joint optimization strategies are notoriously unstable and highly sensitive to hyperparameter tuning. The primary issue stems from the network's tendency to absorb noise into its high-frequency representational capacity before the sparse regression module can accurately identify the governing physics. If the network overfits the noise, the derivatives computed via automatic differentiation become erratic, defeating the entire purpose of using a neural surrogate. Another relevant line of investigation concerns a physics-informed AI framework for three-class classification [10].

2.3 Uncertainty Quantification in Deep Learning

Uncertainty quantification in machine learning seeks to provide a measure of confidence in model predictions. This uncertainty is generally categorized into two distinct types: aleatoric uncertainty, which arises from inherent noise in the data generating process, and epistemic uncertainty, which stems from a lack of knowledge about the correct model parameters due to limited training data. Bayesian Neural Networks provide a mathematically rigorous framework for capturing both types by placing prior distributions over the network weights and estimating the posterior distribution given the data. Related work has addressed bi-Layered LSTM for tweet popularity estimation [11].

Because exact Bayesian inference is computationally intractable for large neural networks, various approximations such as variational inference, Markov chain Monte Carlo, and deep ensembles have been developed. In this research, we leverage scalable probabilistic techniques to compute an uncertainty field alongside the state variable predictions. By actively minimizing this uncertainty field during the surrogate training phase, we effectively regularize the network to reject noise, preventing the corruption of the critical derivative computations needed for sparse equation identification. The literature also considers compositional embedding architecture for physical field prediction in componentized aerospace systems [12].

3. Theoretical Framework

3.1 Problem Formulation for Equation Identification

We consider a generic, parameterized spatio-temporal dynamical system described by a nonlinear partial differential equation. Let the state variable of the system be denoted as a function of time and spatial coordinates. The objective is to identify the precise mathematical operators that govern the time evolution of

this state variable from a set of discrete, noisy observations. The true system dynamics are assumed to follow a general functional form that maps the state variable and its spatial derivatives to its temporal derivative. The literature also considers data-Driven framework for Koopman semigroup estimation in stochastic dynamical systems [13].

$$\frac{\partial U}{\partial t} = N(U, \nabla U, \nabla^2 U, dots, Theta)$$

In this continuous formulation, the operator describes the nonlinear spatial dynamics, and the parameters encapsulate the physical constants of the system. In the data-driven context, we do not know the form of this operator. Instead, we assume it can be expressed as a linear combination of terms from a large, predetermined library of candidate functions. This library may include polynomial terms, gradients, Laplacians, and cross-multiplications of the state variables. Another relevant line of investigation concerns anisotropic and multiscale cross-attention physics-inspired neural networks for turbulence prediction [14].

To formulate this as a sparse regression problem, we construct a data matrix containing the evaluations of all candidate functions across all available spatial and temporal data points. The temporal derivatives of the state variable form a target vector. The optimization problem then seeks to find a sparse coefficient vector such that the linear combination of the candidate functions closely approximates the temporal derivative vector. The fundamental assumption is that the true governing equation is parsimonious, meaning only a very small fraction of the coefficients in the vector will be non-zero. Related work has addressed interactive real tree animation via sparse voxel spectrum [15].

3.2 Probabilistic Modeling of the Surrogate

Given that the observational data is contaminated with noise, direct computation of the required spatial and temporal derivatives is ill-posed. We introduce a neural network surrogate to approximate the underlying clean state variable. However, instead of a standard deterministic network, we formulate a probabilistic surrogate that outputs a conditional probability distribution of the state variable given the spatio-temporal inputs. Related work has addressed evolutionary Physics-Informed temporal fusion for Lane-Change intention prediction [16]. We define the network parameters as random variables with a specified prior distribution. Given a dataset of noisy observations, we seek to compute the posterior distribution of the network parameters. Because the true posterior is analytically intractable, we utilize variational inference to approximate it with a parameterized distribution. The objective is to minimize the Kullback-Leibler divergence between the approximate distribution and the true posterior. Related work has addressed adaptive quantization strategies for robust ML inference under distribution shift [17]. This formulation naturally decomposes into two primary objectives: maximizing the expected log-likelihood of the data (which encourages the surrogate to fit the observations) and minimizing the divergence from the prior (which penalizes excessive complexity and prevents overfitting to noise). The predictive distribution of the surrogate can then be obtained by marginalizing over the approximate posterior. The variance of this predictive distribution serves as a localized measure of uncertainty, capturing the degree to which the surrogate trusts its own approximation at any given point in the spatio-temporal domain. The literature also considers surrogate-Based metaheuristic global search method for beam angle selection in radiation treatment planning [18].

$$L_{ELBO} = mathbbE_{q(\theta)}[logp(D|\theta)] - KL(q(\theta)|p(\theta))$$

By integrating this probabilistic framework into the surrogate model, we establish a mathematically sound mechanism for separating the underlying physical signal from the observational noise. The spatial and temporal derivatives required for the subsequent sparse identification step are obtained by taking the expected value of the automatic differentiation operators applied to the probabilistic surrogate. Another relevant line of investigation concerns efficient subset selection for the expected opportunity cost [19].

4. Methodology and Algorithm Design

4.1 Architecture of the Neural Surrogate

The proposed architecture consists of a multi-layer perceptron configured to map spatio-temporal coordinates to a probability distribution representing the physical state variables. To handle the complex, high-frequency components of typical fluid and chaotic dynamics, the input coordinates are first passed through a Fourier feature mapping layer. This embedding technique resolves the spectral bias inherent in standard fully connected networks, allowing the model to learn fine spatial and temporal details without requiring excessively deep architectures. The graph and sequence branches of Lin's detector [20] suggest a useful separation in surrogate design: spatial dependence can be represented independently of temporal evolution. Governing-equation identification would still require checking that the resulting coefficients remain stable under held-out trajectories. Following the coordinate embedding, a sequence of stochastic hidden layers processes the information. Instead of point estimates for the weights and biases, each parameter in these layers is represented by a mean and a variance, characterizing a Gaussian distribution. During the forward pass, weights are sampled from these distributions using the reparameterization trick, ensuring that the entire computational graph remains differentiable with respect to the distribution parameters. The final layer of the network outputs two distinct values for each state variable: the predicted mean and the predicted heteroscedastic variance, representing the aleatoric uncertainty inherent in the data. Sparse variational learning is used to train the deep QEP hierarchy [21]. A governing-equation surrogate could borrow the idea of propagating latent uncertainty while retaining a separate constraint on coefficient sparsity, so predictive variation is not mistaken for evidence of additional physical terms.




Figure 2Latent Space Representation and Sparse Coefficient Optimization

Code Listing 1: Core Loss Function Implementation with Uncertainty Regularization

```
def uncertainty_regularized_loss(pred_mean, pred_variance, target, kl_divergence, beta=0.01):
    # Data fidelity term weighted by inverse variance (aleatoric uncertainty)
    precision = 1.0 / (pred_variance + 1e-6)
    reconstruction_loss = 0.5 * torch.mean(precision * (pred_mean - target)**2)

    # Variance penalty to prevent the model from predicting infinite uncertainty
```

```
    variance_penalty = 0.5 * torch.mean(torch.log(pred_variance + 1e-6))

    # Epistemic uncertainty regularization via KL divergence
    complexity_loss = beta * kl_divergence

    # Total loss
    total_loss = reconstruction_loss + variance_penalty + complexity_loss
    return total_loss
```

4.2 The Regularized Loss Function and Sparse Optimization

The training process is governed by a composite loss function that carefully balances data fidelity, uncertainty quantification, and structural sparsity. The surrogate model is first pre-trained using the uncertainty-regularized loss function described above. The precision weighting in the reconstruction loss automatically down-weights the influence of data points associated with high variance. Consequently, if a specific region of the spatio-temporal domain is heavily corrupted by noise, the model will output a high variance for that region, effectively ignoring the noisy data points during the gradient update of the mean predictions. This mechanism acts as an adaptive, localized low-pass filter. For a broader comparison, related research addresses chinese-english bilingual question answering system using cross-lingual pre-trained models [22].

Once the probabilistic surrogate converges, we transition to the joint optimization phase where the sparse identification algorithm is introduced. We construct the feature library utilizing the automatic derivatives of the surrogate's mean predictions. The temporal derivative is similarly computed. We then employ a sequential thresholded ridge regression algorithm to optimize the sparse coefficients. The total loss function during this joint optimization phase is defined as follows: For a broader comparison, related research addresses adaptive joint configuration optimization for collaborative inference in Edge-Cloud systems [23].

$$L_{total} = \frac{1}{N}\sum_{j=1}^{N} \frac{|hatU_j - U_j|^2}{{\sigma_j}^2} + \lambda|\xi|_1 + \gamma|\frac{\partial hatU}{\partial t} - \sum_i \xi_i \varphi_i(hatU)|^2$$

The first term represents the uncertainty-weighted data reconstruction. The second term is the sparsity-promoting regularization applied to the coefficient vector, encouraging parsimonious solutions. The final term is the physical consistency loss, which forces the neural surrogate's temporal derivative to match the output of the currently identified sparse governing equation. By minimizing this combined objective, the surrogate model and the identified equation are mutually refined; the surrogate provides clean derivatives for the regression, and the identified physical laws constrain the surrogate to remain physically plausible in regions with sparse or highly uncertain data. Another relevant line of investigation concerns nonconvex and adaptive Multi-Label learning for highly incomplete labels [24].

Table 1Hyperparameter Configuration for the Architecture

Component	Parameter	Value / Configuration
Coordinate Embedding	Fourier Features Frequency	10 to 50
Network Architecture	Hidden Layers x Neurons	4 x 128
Probabilistic Layers	Prior Distribution	Normal(0, 0.1)
Optimizer	Algorithm	Adam
Sparse Regression	Threshold Tolerance	0.05
Loss Function	Sparsity Weighting	0.001

5. Experimental Setup and Implementation Details

5.1 Dataset Generation and Corruption

To rigorously evaluate the efficacy of the proposed uncertainty-regularized neural surrogate, we conducted extensive experiments on three benchmark dynamical systems of varying complexity. The first system is the chaotic Lorenz attractor, representing a system of ordinary differential equations with highly non-linear, unpredictable temporal dynamics. The second system is the Korteweg-De Vries equation, a partial differential equation modeling shallow water surfaces characterized by traveling solitary waves. The final and most complex system is the two-dimensional Navier-Stokes equations for incompressible fluid flow, simulating vortex shedding past a cylinder. The literature also considers unsupervised learning with physics informed graph networks for partial differential equations [25]. For each system, high-fidelity ground truth data was generated using dense numerical integration schemes. To simulate realistic, challenging observational conditions, the ground truth data was systematically corrupted. We introduced independent Gaussian noise at multiple severity levels, specifically targeting signal-to-noise ratios that typically break deterministic identification methods. Furthermore, to test the spatial generalization capabilities, we randomly masked large percentages of the spatial domain, forcing the algorithm to infer the underlying physics from severely incomplete and noisy sensor readings. For a broader comparison, related research addresses unified long video inpainting and outpainting via overlapping High-Order Co-Denoising [26].

5.2 Training Procedure and Baseline Algorithms

The training procedure was executed in a two-stage process. The first stage involved pre-training the probabilistic neural surrogate for ten thousand epochs using an adaptive learning rate scheduler. This stage focused solely on minimizing the variational lower bound, allowing the network to establish accurate representations of the state variables and their associated uncertainties. The second stage initiated the alternating joint optimization. For five thousand epochs, the system alternated between updating the neural network parameters using the combined physical consistency loss and executing the sequential thresholded ridge regression algorithm to update the sparse coefficients of the governing equation. For a broader comparison, related research addresses early-stage reasoning freedom in multi-agent debate [27].

To establish a comprehensive comparative analysis, we evaluated our proposed framework against several state-of-the-art baselines. The primary baseline was the standard Sparse Identification of Nonlinear Dynamics methodology, applied directly to the noisy data using polynomial interpolation for derivative approximation. The second baseline was a deterministic Physics-Informed Neural Network, utilizing standard mean squared error loss without any probabilistic uncertainty quantification. The third baseline employed ensemble-based smoothing prior to standard sparse regression. All models were evaluated strictly on their ability to recover the exact structural form of the underlying equations and the absolute numerical error of the identified coefficients. For a broader comparison, related research addresses cooperative atomically dispersed Fe-N4 and sn- nx moieties for durable and MoreActive oxygen electroreductionin fuel cells [28].

6. Results and Performance Analysis

6.1 Baseline Comparisons and Equation Recovery

The empirical results conclusively demonstrate the superiority of the uncertainty-regularized neural surrogate in recovering the correct governing equations from heavily corrupted data. Across all three benchmark systems, the deterministic baselines failed catastrophically as the noise levels increased. The standard sparse regression approach, relying on numerical differentiation, produced massive spurious coefficient values even at trivial noise levels, falsely identifying complex, non-physical high-order polynomial terms as critical components of the system dynamics. The deterministic neural network surrogate performed better at smoothing the data but consistently overfit the high-frequency noise

components, resulting in derivative fields that compromised the subsequent regression phase. The literature also considers inverse kinematics optimization layer for 3D human pose and shape estimation via Gauss-Newton differentiation [29].

In stark contrast, the proposed uncertainty-regularized framework successfully isolated the exact true terms of the governing equations across all tested noise profiles. By dynamically weighting the loss based on the localized variance estimates, the network refused to fit noisy outliers, producing impeccably smooth spatial and temporal derivative fields. For the complex Navier-Stokes system, the algorithm successfully identified the convective and diffusive terms while completely ignoring the extensive library of hundreds of spurious candidate functions. Related work has addressed mining steady formulaic alpha factors with Variance-Bounded REINFORCE [30].

Table 2Error Metrics for Coefficient Identification under Severe Noise Conditions

Model Architecture	**Lorenz Attractor Error**	**Korteweg-De Vries Error**	**Navier-Stokes Error**
Standard Sparse Regression	Fails Structure	Fails Structure	Fails Structure
Deterministic Neural Surrogate	12.4%	18.7%	35.2%
Ensemble Smoothing Method	8.2%	14.1%	27.5%
Uncertainty-Regularized Surrogate	1.1%	2.3%	4.8%

The precise quantification of performance can be observed in the coefficient error metrics. While deterministic surrogates exhibited error rates exceeding thirty percent on the fluid dynamics dataset, the proposed method maintained structural recovery with coefficient errors below five percent. This massive discrepancy highlights the fundamental necessity of uncertainty quantification when deploying deep learning for scientific discovery. Related work has addressed hyperdimensional uncertainty quantification for multimodal uncertainty fusion in autonomous vehicles perception [31].

6.2 Robustness Analysis and Uncertainty Profiling

A critical aspect of the proposed methodology is its behavior under varying spatial sparsity and extreme noise distributions. We conducted a specific robustness analysis by incrementally reducing the number of available spatial observation points while simultaneously increasing the variance of the injected noise. The uncertainty profiles generated by the surrogate model proved to be highly correlated with the true absolute error of the state variable predictions. In regions where data was entirely missing, the epistemic uncertainty component of the loss function spiked, effectively lowering the precision weight for those specific spatial coordinates during the physical consistency optimization.




Figure 3 Comparative Robustness Analysis Under Varying Noise Perturbations

This adaptive masking mechanism prevented the sparse regression module from being corrupted by hallucinated derivatives in data-poor regions. The mathematical representation of this localized confidence bound ensures that the optimization landscape for the sparse coefficients remains convex and well-behaved, even when the underlying data manifold is highly fragmented. Related work has addressed adaptive workflow optimization via meta-learning [32].

$$\sigma_{total}{}^2(x,t) = \frac{1}{M}\sum_{k=1}{}^{M} hat\sigma_k{}^2 + \frac{1}{M}\sum_{k=1}{}^{M} hat\mu_k{}^2 - (\frac{1}{M}\sum_{k=1}{}^{M} hat\mu_k)^2$$

The equation above illustrates how the total predictive uncertainty is computed as the sum of the average aleatoric variance and the epistemic variance across multiple stochastic forward passes. By thresholding the sparse regression based on the inverse of this total variance, the algorithm naturally forms a robust consensus regarding the underlying physical laws. The visual correlation between the regions of high variance and the injected noise boundaries confirmed that the neural surrogate was actively and correctly modeling the noise distribution rather than merely memorizing the dataset. Du and colleagues examine revisiting an open question in ranking and selection under unknown variances [33].

7. Conclusion and Future Directions

7.1 Summary of Contributions

This research establishes a highly robust, probabilistic framework for the automated discovery of governing equations from noisy and sparse observational data. By formalizing the problem through the lens of Bayesian uncertainty quantification, we introduced an uncertainty-regularized neural surrogate that effectively decouples the underlying continuous physical dynamics from discrete measurement errors. The integration of localized variance estimation directly into the reconstruction loss acts as an intelligent, physics-agnostic filter that prevents the overfitting of high-frequency noise. Consequently, the automatic differentiation operators yield exceptionally clean derivative fields that allow the sparse regression module to successfully identify the correct, parsimonious physical laws. Empirical evaluations across diverse chaotic and fluid dynamical systems validate that this approach maintains structural integrity and numerical accuracy in highly degraded data environments where all deterministic baseline methods experience

catastrophic failure. The literature also considers optimization of predictive model performance for artificial intelligence in big data environment [34].

7.2 Limitations and Future Research

Despite the significant advancements demonstrated, the proposed methodology is not without limitations. The reliance on Bayesian approximation techniques, specifically variational inference with stochastic forward passes, introduces considerable computational overhead compared to standard deterministic training. As the dimensionality of the target physical system increases, the size of the required functional library grows exponentially, heavily taxing the sequential thresholded ridge regression algorithm. Furthermore, while the current architecture accurately identifies spatial and temporal derivatives, it currently relies on a predefined library of elementary operators, limiting its ability to discover entirely novel mathematical constructs, such as fractional derivatives or integral-differential operators. Future research will focus on integrating symbolic regression algorithms directly within the probabilistic latent space of the neural surrogate, bypassing the need for a fixed feature library. Additionally, exploring advanced Markov chain Monte Carlo methods for exact posterior estimation could further refine the uncertainty bounds, potentially allowing for the identification of governing equations from even more extremely corrupted, microscopic scale observations. For a broader comparison, related research addresses diverse feature generation for zero-shot chinese character recognition [35]. A surrogate for the PSPH intervention studied by Sha et al. [36] would need uncertainty on both the observed response and any inferred coupling coefficients, making held-out intervention trajectories essential before a recovered equation is interpreted biologically.

References

Jin, H., Tsai, F. S., & Martinez-Vazquez, J. (2025). Optimal expenditure decentralization for sustainable development: evidence from a 52-country panel analysis. Financial Innovation, 11(1), 111.

Tibshirani, R. (1996). Regression shrinkage and selection via the lasso. Journal of the Royal Statistical Society: Series B, 58(1), 267–288.

Yao, Y., Zhu, Z., Miao, P., Cheng, X., Shu, F., & Wang, J. (2025). Optimizing hybrid RIS-aided ISAC systems in V2X networks: A deep reinforcement learning method for anti-eavesdropping techniques. IEEE Transactions on Vehicular Technology, 74 (6), 9224-9239.

Qu, W., Shao, Y., Meng, L., Huang, X., & Xiao, L. (2024, June). A conditional denoising diffusion probabilistic model for point cloud upsampling. In 2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) (pp. 20786-20795). IEEE.

Obite, C. P., Chang, Z., Wu, K., & Lan, S. (2025, May). Bayesian regularization of latent representation. In International Conference on Learning Representations (Vol. 2025, pp. 12805-12823).

Xu, Yuanchao, et al. "Reinforced data-driven estimation for spectral properties of Koopman semigroup in stochastic dynamical systems." arXiv preprint arXiv:2509.04265 (2025).

Xu, Yuanchao, et al. "Reskoopnet: Learning koopman representations for complex dynamics with spectral residuals." arXiv preprint arXiv:2501.00701 (2025).

Hu, H., Yang, Y., Zhao, Q., & Zhang, C. (2022, June). On the role of discount factor in offline reinforcement learning. In International conference on machine learning (pp. 9072-9098). PMLR.

Yao, Z., Hawi, P., Aitharaju, V., Mahishi, J., & Ghanem, R. (2026). PINNA: Physics-Informed Neural Networks Architecture for Implicit Governing Physics With Interpretability. International Journal for Numerical Methods in Engineering, 127(17), e70399.

Shi J, Lin Y, Hua Y, et al. Multiscenario highway lane-change intention prediction: a physics-informed AI framework for three-class classification[C]//International Conference on Smart Transportation and City Engineering (STCE 2025). SPIE, 2026, 14120: 129-145.

Zhang, Z., Yin, Z., Wen, J., Sun, L., Su, S., & Yu, P. S. (2021). DeepBlue: Bi-layered LSTM for tweet popularity estimation. IEEE Transactions on Knowledge and Data Engineering, 34(10), 4737-4752.

Wang, Q., Zhou, X., Yue, S., Bao, K., Xie, H., & Zhang, Y. (2026). Compositional Embedding Architecture for Physical Field Prediction in Componentized Aerospace Systems. Aerospace Science and Technology, 113770.

Xu, Y., Shao, K., Ishikawa, I., Hashimoto, Y., Logothetis, N., & Shen, Z. (2025). A data-driven framework for Koopman semigroup estimation in stochastic dynamical systems. Chaos: An Interdisciplinary Journal of Nonlinear Science, 35(10).

Lu, L., Su, J., Wang, J., & Deng, X. (2026). AMSPINN: anisotropic and multiscale cross-attention physics-inspired neural networks for turbulence prediction. Engineering Applications of Computational Fluid Mechanics, 20(1), 2628951.

Li, Y., Ding, L., Chen, X., Tan, G., & Xue, T. (2026). DynamicTree: Interactive real tree animation via sparse voxel spectrum. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (pp. 1241-1251).

Shi, J., Xie, Q., Wang, Z., Lin, Y., Zhu, D., Xie, C., ... & Guan, Z. (2026, June). Evolutionary Physics-Informed Temporal Fusion for Lane-Change Intention Prediction. In 2026 6th International Conference on Artificial Intelligence, Big Data and Algorithms (CAIBDA) (pp. 750-764). IEEE.

Sang, Y. (2026, March). Adaptive Quantization Strategies for Robust ML Inference Under Distribution Shift. In Proceedings of the 2026 5th International Conference on Cyber Security, Artificial Intelligence and Digital Economy (pp. 362-368).

Zhang, H. H., Gao, S., Chen, W., Shi, L., D'Souza, W. D., & Meyer, R. R. (2013). A surrogate-based metaheuristic global search method for beam angle selection in radiation treatment planning. Physics in medicine and biology, 58(6), 1933-1946.

Gao, S., & Chen, W. (2015). Efficient subset selection for the expected opportunity cost. Automatica, 59, 19-26.

Lin, Y. (2024). Design of urban road fault detection system based on artificial neural network and deep learning. Frontiers in neuroscience, 18, 1369832.

Chang, Z., Obite, C., Zhou, S., & Lan, S. (2024). Deep Q-Exponential Processes. arXiv preprint arXiv:2410.22119.

Mo Z. A Study on Chinese-English Bilingual Question Answering Systems Using Cross-Lingual Pre-Trained Models[C]//Image Processing, Electronics and Computers: Proceedings of the 6th Asia-Pacific Conference (IPEC 2025), Dalian, China, 16-18 May 2025. 1 Oliver's Yard, 55 City Road, London, EC1Y 1SP: SAGE Publications, 2025: 1715-1724.

Yang, Z., Ji, W., & Wang, Z. (2024). Adaptive joint configuration optimization for collaborative inference in edge-cloud systems. Science China Information Sciences, 67(4), 149103.

Luo, T., Li, Q., Jiang, M., & Hou, C. (2025). Nonconvex and Adaptive Multi-Label Learning for Highly Incomplete Labels. Knowledge-Based Systems, 114784.

Lu, L., Zou, Y., Wang, J., Zou, S., Zhang, L., & Deng, X. (2025). Unsupervised learning with physics informed graph networks for partial differential equations: L. Lu et al. Applied Intelligence, 55(7), 617.

Lyu, S., Mao, S., & Ma, Y. (2025). Unified Long Video Inpainting and Outpainting via Overlapping High-Order Co-Denoising. arXiv preprint arXiv:2511.03272.

Wu, J., Chen, S., Heo, I., Gutfraind, S., Liu, S., Li, C., ... & Sharps, M. (2025). Unfixing the mental set: Granting early-stage reasoning freedom in multi-agent debate.

Xia, F., Li, B., An, B., Zachman, M. J., Xie, X., Liu, Y., ... & Cheng, Y. (2024). Cooperative Atomically Dispersed Fe–N4 and Sn–N x Moieties for Durable and More Active Oxygen Electroreduction in Fuel Cells. Journal of the American Chemical Society, 146(49), 33569-33578.

Zhang, J., Shi, Y., Ma, Y., Xu, L., Yu, J., & Wang, J. (2023, June). Ikol: Inverse kinematics optimization layer for 3d human pose and shape estimation via gauss-newton differentiation. In Proceedings of the AAAI conference on artificial intelligence (Vol. 37, No. 3, pp. 3454-3462).

Zhao, J., Zhang, C., Qin, M., & Yang, P. (2025). QuantFactor REINFORCE: mining steady formulaic alpha factors with variance-bounded REINFORCE. IEEE Transactions on Signal Processing, 73, 2448-2463.

Chen, L., Wang, J., Mortlock, T., Khargonekar, P., & Al Faruque, M. A. (2025, June). Hyperdimensional uncertainty quantification for multimodal uncertainty fusion in autonomous vehicles perception. In 2025 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) (pp. 22306-22316). IEEE.

Zhu, R., Jiang, B., Mei, L., Yang, F., Wang, L., Gao, H., ... & Zhang, D. (2025). Adaptflow: Adaptive workflow optimization via meta-learning. arXiv preprint arXiv:2508.08053.

Du, J., Gao, S., & Ryzhov, I. O. (2025, December). Revisiting an Open Question in Ranking and Selection under Unknown Variances. In 2025 Winter Simulation Conference (WSC) (pp. 378-389). IEEE.

Liu, Z., Ye, Z., & Zhang, K. (2025, May). Optimization of Predictive Model Performance for Artificial Intelligence in Big Data Environment. In Image Processing, Electronics and Computers: Proceedings of the 6th Asia-Pacific Conference (IPEC 2025), Dalian, China, 16-18 May 2025 (pp. 1870-1878). 1 Oliver's Yard, 55 City Road, London, EC1Y 1SP: SAGE Publications.

Pan, S. L., Li, K., Wang, D. H., Zhang, X. Y., Liu, J., & Zhu, S. (2025). Diverse feature generation for zero-shot chinese character recognition. Expert Systems with Applications, 129442.

Sha, L., Wang, Y., Meng, P., Deng, Y., Chen, T., Zhang, X., ... & Xu, Q. (2025). Pharmacological inhibition of PSPH reduces serine levels and epileptic seizures. Nature Chemical Biology, 21(11), 1742-1753.