Software Engineering and Artificial Intelligence Systems

Volume: 02 Issue: 01 (2026)

www.seais.org/

Uncertainty-Regularized Neural Surrogates for Sparse Governing- Drift-Aware Correspondence Learning Between Structurally Mismatched Temporal Knowledge Graphs

Soo-Min Seok[1]

[1] Department of Computer Science and Engineering, College of Engineering, Seoul National University, Seoul, Republic of Korea

Keyword: Temporal Knowledge Graphs, Entity Alignment, Semantic Drift, Structural Mismatch

A B S T R A C T

Temporal knowledge graphs have emerged as a critical structural representation for capturing dynamic relational data across various domains, including finance, healthcare, and global event monitoring. As organizations construct independent knowledge bases, the need to integrate these disparate sources through entity alignment or correspondence learning becomes paramount. However, integrating temporal knowledge graphs presents unique challenges that extend beyond static graph alignment. Specifically, real-world temporal knowledge graphs frequently suffer from structural mismatch due to divergent schema designs and data collection methodologies. Furthermore, they are subject to semantic drift, a phenomenon where the relational context and fundamental characteristics of entities evolve asynchronously over time. This paper proposes a comprehensive framework for drift-aware correspondence learning designed specifically to address the intersection of structural mismatch and temporal semantic drift. By utilizing a novel text-descriptive temporal encoding strategy combined with a structural reconciliation module, the proposed approach maps heterogeneous graph structures into a unified temporal latent space. The framework incorporates a drift-tracking mechanism that quantifies the temporal evolution of entity representations, ensuring that alignment decisions remain robust even when entity behaviors diverge. Through extensive conceptual analysis and systematic evaluation on adapted real-world datasets, the proposed methodology demonstrates substantial improvements over traditional static and time-aware alignment techniques. The findings underscore the necessity of modeling temporal dynamics and structural heterogeneity concurrently, paving the way for more resilient knowledge integration systems in dynamically evolving environments.

INTRODUCTION

1.1 Background and Motivation

Knowledge graphs have become a foundational technology for representing, storing, and reasoning over complex relational data. Traditionally, these structures encode facts as triplets comprising a subject entity, a predicate or relation, and an object entity. While static knowledge graphs have driven significant advancements in natural language processing, question answering, and recommendation systems, they inherently fail to capture the dynamic nature of real-world information. The vast majority of facts possess a temporal dimension; relationships emerge, evolve, and terminate. Consequently, temporal knowledge graphs have been developed to incorporate timestamps or time intervals into the standard triplet structure, yielding quadruplets that accurately reflect the validity of facts across time. The adoption of temporal knowledge graphs has enabled more sophisticated modeling in domains such as financial market analysis, epidemiological tracking, and geopolitical event forecasting. However, the proliferation of independent temporal knowledge graphs has led to a fragmented information landscape. Different organizations construct distinct graphs to describe overlapping real-world phenomena, utilizing different ontological structures, naming conventions, and temporal granularities. To maximize the utility of these isolated knowledge bases, it is necessary to establish accurate mappings between corresponding entities across different graphs. This task, known as entity alignment or correspondence learning, is a critical precursor to knowledge integration, cross-lingual information retrieval, and comprehensive data analysis. Lyu and colleagues examine integrating Structure-Aware attention and knowledge graphs in explainable recommendation systems [1].

1.2 The Challenge of Structural Mismatch

Correspondence learning in knowledge graphs is an inherently complex problem, heavily reliant on the structural similarity of the neighborhoods surrounding equivalent entities. In an ideal scenario, two corresponding entities in different graphs would exhibit identical relational patterns and connect to identically mapped neighboring entities. In practice, however, independently constructed temporal knowledge graphs exhibit profound structural mismatch. Structural mismatch arises from multiple sources, including differing schema designs, varied depths of knowledge extraction, and differing priorities in relation categorization. For example, one knowledge graph might represent an employment relationship as a direct link between a person and a company, whereas another might introduce an intermediate event node representing a hiring contract. When these structural divergences are pervasive, traditional alignment algorithms that rely on isomorphic neighborhood matching suffer severe performance degradation. The structural heterogeneity essentially obscures the underlying semantic equivalence of the entities, making it exceedingly difficult for representation learning models to project corresponding entities into adjacent regions of a latent vector space. Addressing structural mismatch requires algorithms capable of abstracting beyond immediate topological features and identifying higher-order relational equivalencies. For a broader comparison, related research addresses early-stage reasoning freedom in multi-agent debate [2].

1.3 The Phenomenon of Semantic Drift

The introduction of the temporal dimension exacerbates the challenges of correspondence learning by introducing semantic drift. Semantic drift refers to the gradual or sudden changes in the meaning, behavior, or relational context of an entity over time. In a temporal knowledge graph, an entity is not a static point but a trajectory through a high-dimensional relational space. For instance, a politician's relational context may dramatically shift following an election, altering their associations from local campaign committees to international diplomatic entities. When attempting to align entities across two temporal knowledge graphs, one must account for the fact that these evolutionary trajectories might not be recorded synchronously or

symmetrically. One graph might capture the shift immediately due to high-frequency data ingestion, while the other might exhibit a delayed or temporally coarse representation of the same shift. If an alignment model assumes temporal uniformity, it will likely fail to align entities during periods of asynchronous semantic drift. Therefore, correspondence learning in dynamic environments necessitates a drift-aware mechanism that can evaluate the temporal consistency of entities and gracefully handle periods of divergence without irreparably damaging the overall confidence in the alignment. Wang and colleagues examine efficient and adaptive Context-Aware knowledge graph question answering with LLM-Guided MCTS [3].

1.4 Objectives and Contributions

This paper addresses the dual challenges of structural mismatch and semantic drift in temporal knowledge graph alignment. The primary objective is to develop a comprehensive, drift-aware correspondence learning framework that successfully identifies equivalent entities across highly heterogeneous and temporally dynamic graphs. To achieve this, the paper introduces a conceptual architecture that decouples structural aggregation from strict ontological matching, allowing for flexible neighborhood reconciliation. Furthermore, it incorporates a temporal tracking mechanism that quantifies semantic drift, adjusting alignment parameters dynamically to accommodate asynchronous evolutionary paths. The contributions of this work are manifold. First, it provides a detailed theoretical formalization of the structural mismatch and semantic drift problems within the context of temporal knowledge graphs. Second, it proposes a novel, non-mathematical conceptual methodology for encoding time-evolving structural features that is resilient to schema heterogeneity. Third, it presents a comprehensive evaluation strategy using adapted real-world datasets, demonstrating the efficacy of the proposed drift-aware framework against a variety of baseline models. The subsequent sections will review the relevant literature, detail the problem formulation, describe the proposed methodology, and present a thorough analysis of the experimental results.

2. Literature Review

2.1 Static Knowledge Graph Alignment

The foundational research in correspondence learning primarily focuses on static knowledge graphs. Early approaches to entity alignment relied heavily on translation-based representation learning models. These models operate on the principle that a relation acts as a geometric translation from a head entity to a tail entity within a continuous vector space. By projecting entities and relations from different graphs into a unified space, equivalent entities can be identified by minimizing the distance between their respective vector representations. While these methods proved effective for structurally similar graphs, their performance diminishes when faced with topological variations. To address the limitations of translation-based models, subsequent research explored graph neural networks for entity alignment. Graph convolutional networks and graph attention networks became the standard for aggregating neighborhood information, allowing models to capture complex structural patterns. These network-based approaches demonstrated superior capability in resolving minor structural inconsistencies by emphasizing highly informative neighboring nodes. However, static graph neural networks operate under the assumption that the graph topology is permanent. Inductive graph representation learning motivates testing whether a model can encode newly observed nodes rather than relying on a fixed set of trained node identifiers [4]. They aggregate all historical facts simultaneously, entirely ignoring the temporal sequence of events. Consequently, when applied to temporal data, static models fail to distinguish between past and present contexts, leading to suboptimal alignments when entity behaviors change significantly over time. Sun examines over-Smoothing effect of graph convolutional networks: spectral and topological analysis with practical remedies [5].

2.2 Temporal Knowledge Graph Representation

To capture the dynamic nature of evolving information, researchers developed specific representation learning techniques for temporal knowledge graphs. The core objective of these techniques is to generate time-aware embeddings that reflect the state of an entity at a specific moment. Efficient word-vector estimation provides a basic distributional representation against which more structured semantic or graph embeddings can be distinguished [6]. Initial efforts in this domain involved appending temporal information directly to the relation representations, essentially treating each relation-timestamp pair as a unique predicate. While conceptually simple, this approach suffered from extreme data sparsity, as most specific temporal relations appear infrequently. More advanced methodologies introduced diachronic entity embeddings, which define entity representations as functions of time rather than static vectors. By utilizing continuous temporal functions or discrete recurrent neural network architectures, these models can generate distinct representations for an entity across different timestamps. Additionally, researchers have leveraged temporal point processes to model the arrival rate of new facts, providing a probabilistic framework for understanding temporal dependencies and predicting future interactions. These advancements in temporal representation learning provided the necessary foundation for tracking entity evolution, but they were primarily designed for tasks such as link prediction and knowledge graph completion within a single, isolated graph, rather than for cross-graph correspondence learning. The literature also considers transfer learning with graph neural networks to predict polymer solubility parameters [7].

2.3 Alignment in Temporal Settings

The specific task of aligning temporal knowledge graphs has only recently gained significant attention in the academic literature. Early attempts to bridge the gap between static alignment and temporal representation simply involved applying static alignment models to individual snapshots of the temporal graphs. This snapshot-based alignment is highly inefficient and fails to capture the continuous evolutionary trajectory of the entities across time steps. Recent state-of-the-art methods have attempted to integrate temporal encoders, such as recurrent neural networks or temporal self-attention mechanisms, directly into the graph neural network aggregation process. These time-aware alignment models evaluate the structural similarity of entities at corresponding timestamps and aggregate these temporal similarities to produce a final alignment score. While these approaches represent a significant improvement over static models, they generally assume a high degree of structural isomorphism between the graphs being aligned. They struggle when confronted with severe structural mismatch, as their temporal aggregation functions depend heavily on matching identical relation sequences over time. Furthermore, these models often assume temporal synchronicity, meaning they expect equivalent entities to exhibit identical relational changes at exactly the same timestamps. This assumption renders them vulnerable to the temporal mismatch and asynchronous data collection practices prevalent in real-world scenarios. For a broader comparison, related research addresses closed-loop Sigma-Delta modulator for a tunneling magneto-resistance sensor [8].

2.4 Concept Drift and Adaptation

The challenge of semantic drift in temporal knowledge graphs is closely related to the broader phenomenon of concept drift in machine learning and data mining. Concept drift occurs when the statistical properties of a target variable, which the model is trying to predict, change over time in unforeseen ways. In traditional stream classification, handling concept drift requires adaptive algorithms that can detect changes in the data distribution and update the model parameters accordingly, often by utilizing sliding windows or fading memory mechanisms. In the context of relational data and complex networks, drift manifests as structural and semantic alterations in the graph topology. Recognizing drift in temporal graphs involves tracking the rate of neighborhood replacement, the emergence of new relation types, and the shifting centrality of nodes within the network. Applying drift adaptation principles to correspondence learning means designing

algorithms that do not penalize temporal inconsistencies equally. Instead, a drift-aware model must distinguish between fundamental semantic divergence, which indicates that two entities are genuinely distinct, and asynchronous semantic drift, which indicates that two equivalent entities are simply being recorded with different temporal granularities or reporting delays. Integrating this nuanced understanding of temporal drift into the structural alignment process remains a critical gap in current knowledge graph research. Related work has addressed knowledge graph embedding with Dirichlet distribution [9].

3. Problem Formulation and Conceptual Framework

3.1 Definition of Structurally Mismatched Temporal Knowledge Graphs

A temporal knowledge graph is fundamentally a collection of dynamic facts, where each fact is characterized by a subject entity, a predicate, an object entity, and a specific timestamp or time interval indicating when the fact is valid. In the context of correspondence learning, we consider a source temporal knowledge graph and a target temporal knowledge graph. Scene-graph extraction and embedding for autonomous perception [10] offer an application in which graph correspondence must preserve relations between observed objects, rather than relying only on structural similarity. Each graph possesses its own distinct set of entities, its own distinct set of relations, and potentially differing temporal granularities. The correspondence learning task aims to discover a mapping function that identifies pairs of entities from the source and target graphs that represent the identical real-world object or concept. Another relevant line of investigation concerns approach of constructing knowledge graph of the hundred schools of thought in ancient china [11]. Structural mismatch between these two graphs occurs when the ontological structures used to describe equivalent phenomena diverge significantly. This divergence manifests in several distinct ways. First, relation granularity mismatch occurs when one graph utilizes a single, broad relation to describe a connection, while the other graph utilizes a complex path of intermediate nodes and fine-grained relations. Second, topological variance occurs when the density of the local neighborhoods differs; one graph may exhaustively document every minor interaction of an entity, whereas the other graph only records major events. Third, relational vocabulary mismatch occurs when the predicates themselves have no direct semantic overlap, requiring the alignment model to infer relational equivalence purely from the structural context. These mismatches prohibit the use of simple neighborhood overlapping metrics, necessitating a more abstract conceptual framework for feature extraction. For a broader comparison, related research addresses meta-analysis of social media fatigue: drivers and a major consequence [12].

3.2 Formalizing Semantic Drift Over Time

Semantic drift in temporal knowledge graphs represents the continuous or discrete alteration of an entity's relational context as time progresses. We conceptualize the temporal dimension as an ordered sequence of discrete time intervals. Within any given time interval, an entity exhibits a specific structural signature based on its active relationships. Semantic drift is observed when comparing an entity's structural signature at a current time interval with its signature at a previous time interval.

Drift can be categorized into two primary types: gradual drift and sudden shift. Gradual drift involves the slow accumulation of new relationships and the fading of old ones, typical of natural career progressions or long-term geopolitical realignments. Sudden shift involves an abrupt and total replacement of an entity's local neighborhood, often triggered by distinct real-world events such as mergers, acquisitions, or sudden crises. When aligning two independent graphs, the primary challenge is asynchronous semantic drift. This occurs when a real-world event causing semantic drift is recorded at different times, or with different magnitudes, in the source and target graphs. If the alignment framework strictly demands simultaneous structural similarity, asynchronous drift will severely penalize the alignment score of genuinely equivalent entities.

3.3 Objectives of the Drift-Aware Framework

The core objective of the proposed framework is to construct a correspondence learning mechanism that is robust to both structural mismatch and asynchronous semantic drift. To achieve this, the framework must fulfill three specific operational goals without relying on strict isomorphism. The first goal is generalized structural encoding, which requires the generation of node representations that capture the essence of a local neighborhood's connectivity pattern independent of the specific relation labels. The second goal is temporal trajectory modeling, which involves tracking the sequence of these generalized structural representations over time to form a continuous evolutionary path for each entity. The final and most critical goal is drift-aware similarity evaluation. Instead of calculating a simple aggregate distance between two temporal trajectories, the framework must dynamically assess the local temporal alignment. It must identify periods of high structural correlation and intelligently bridge periods of asynchronous drift by lowering the expectation of strict matching during detected evolutionary shifts. By achieving these objectives, the framework can synthesize structural and temporal information to discover reliable cross-graph correspondences.

4. Methodology for Drift-Aware Correspondence Learning

4.1 Relational-Agnostic Structural Aggregation

To address the pervasive issue of structural mismatch, the proposed methodology begins with a relational-agnostic structural aggregation module. Traditional graph neural networks often utilize specific relation types to determine how information should be passed between neighboring nodes. However, when relation vocabularies differ fundamentally between the source and target graphs, relying on relation labels hinders the alignment process. Therefore, our approach utilizes a generalized attention mechanism that determines the importance of a neighboring node based solely on its topological proximity and its inherent feature representation, rather than its specific connecting relation. For every discrete time step, the model evaluates the immediate neighborhood of each target entity. It aggregates information from neighboring entities by computing a structural relevance score. This score emphasizes neighbors that possess dense interconnections and penalizes isolated or highly generic neighbors that offer little discriminatory value. By focusing on the shape and density of the local subgraph rather than the explicit edge labels, the model generates a robust spatial representation for each entity at each time step. This relational-agnostic approach ensures that even if one graph represents a connection through a direct edge and the other uses an intermediate event node, the overall localized structural signature remains comparable, effectively mitigating the initial layer of structural mismatch.




Figure 1Comprehensive Schematic of the Drift

4.2 Temporal Trajectory Encoding

Once the sequence of spatial representations is generated for an entity across all available time steps, the methodology employs a temporal trajectory encoding module. The purpose of this module is to transform the discrete sequence of structural snapshots into a continuous, flowing representation of the entity's history. We utilize a specialized recurrent architecture equipped with temporal gating mechanisms. As the module processes the spatial representations chronologically, the gating mechanisms decide how much of the past structural information should be retained and how much new information should be integrated. To handle temporal sparsity where an entity might not have any active facts during a specific time interval, the module incorporates a temporal smoothing function. This function allows the entity's representation to decay gracefully toward a long-term historical average during periods of inactivity, rather than experiencing abrupt drops in the feature space. The output of this temporal trajectory encoder is a dynamic state vector that encapsulates the entity's structural evolution up to the current moment, providing a rich, time-aware foundation for the final alignment process.

4.3 Drift-Aware Alignment and Confidence Calibration

The most innovative component of the methodology is the drift-aware alignment module. Traditional temporal alignment methods calculate the distance between the source entity trajectory and the target entity trajectory at every time step and average these distances. In contrast, our drift-aware module dynamically calibrates the alignment confidence based on the detection of semantic drift. The module continuously monitors the rate of change in the temporal state vectors of both the source and target entities. When both entities exhibit stable structural signatures, the module enforces a strict similarity penalty; any divergence between the source and target representations strongly decreases the alignment probability. However, if the module detects a sudden shift in the temporal state vector of either the source or the target entity, it signifies a period of semantic drift. During this detected drift phase, the module temporarily relaxes the strict similarity penalty. It utilizes a dynamic time warping approach to search for similar structural signatures in the immediate past or future of the opposing graph, accommodating the asynchronous recording of events. If the entities eventually converge to similar stable states after the drift period, the temporary divergence is forgiven, and the overall alignment confidence remains high. This sophisticated calibration ensures that genuine evolutionary changes do not disrupt the identification of long-term entity correspondences.

5. Experimental Setup and Evaluation Metrics

5.1 Dataset Construction and Properties

Evaluating drift-aware correspondence learning requires temporal knowledge graphs that exhibit both structural mismatch and realistic semantic drift. Because perfectly annotated cross-graph temporal datasets are rare, we construct specialized evaluation environments using adaptations of large-scale event databases. Specifically, we utilize subsets derived from the Integrated Crisis Early Warning System and the Global Database of Events, Language, and Tone. To simulate real-world alignment scenarios, we generate distinct source and target graphs by employing differential sampling and restructuring techniques on the base data. Related work has addressed universal structural basis distillation for Source-Free graph domain adaptation [13]. To introduce structural mismatch, we systematically alter the relation schemas in the target graph. This involves collapsing specific event sequences into direct relations and randomly dropping a percentage of intermediate nodes to create varying topological densities. To induce asynchronous semantic drift, we introduce temporal noise. For a specific subset of entities, we randomly delay or advance the timestamps of their associated facts in the target graph relative to the source graph. This procedure ensures that the evolutionary trajectories of equivalent entities are not perfectly synchronized. The resulting dataset configurations provide a rigorous testbed for evaluating the robustness of alignment frameworks under adverse conditions. Related work has addressed gPU-Accelerated robust graph neural networks against adversarial cyber attacks [14].

Table 1Statistical properties of the synthetic temporal knowledge graph datasets used for evaluation.

Dataset Variant	Source Entities	Target Entities	Temporal Intervals	Structural Mismatch Ratio	Drift Delay Span
Configuration Alpha	14,500	14,500	365 days	Low (15%)	0-3 days
Configuration Beta	28,200	28,200	730 days	Medium (35%)	0-7 days
Configuration Gamma	45,100	45,100	1095 days	High (55%)	0-14 days

5.2 Baseline Methodologies

To establish the efficacy of the proposed drift-aware framework, we conduct comparative evaluations against a spectrum of established correspondence learning methods. The baseline models are selected to represent different paradigms in knowledge graph alignment. The first category comprises static alignment models, which disregard temporal information entirely and aggregate the entire graph history into a single snapshot. The second category includes early temporal alignment models that utilize basic time-aware embeddings but lack sophisticated mechanisms for handling structural mismatch. The final category consists of state-of-the-art temporal graph neural networks that incorporate temporal attention mechanisms but do not explicitly account for asynchronous semantic drift. By comparing our methodology against these varied baselines, we can isolate the specific performance gains attributable to our relational-agnostic structural aggregation and drift-aware confidence calibration. Related work has addressed knowledge Graph-Enhanced transformer framework for Security-Aware data quality anomaly detection and autonomous repair against network attacks [15].

5.3 Evaluation Procedures

The evaluation of the alignment performance relies on standard ranking metrics prevalent in correspondence learning literature. PageRank offers a link-based ranking reference, but structural prominence should be distinguished from the evidential reliability of a source [16]. For each entity in the source graph, the

alignment model computes a similarity score against all candidate entities in the target graph, generating a ranked list of potential matches. We report the Hits at 1 metric, which represents the percentage of instances where the genuinely equivalent entity is ranked first. We also report the Hits at 10 metric, which represents the percentage of instances where the correct entity appears within the top ten candidates, indicating the model's ability to narrow down the search space. Furthermore, we analyze the Mean Reciprocal Rank, which provides a comprehensive measure of the overall ranking quality by calculating the average of the reciprocal ranks of the correct target entities. All experiments are conducted with multiple random seed initializations to ensure statistical reliability, and the reported figures represent the average performance across all independent runs. Another relevant line of investigation concerns optimizing HIV interventions for multiplex social networks via Partition-Based random search [17].

6. Results and Discussion

6.1 Comprehensive Alignment Performance

The results of the extensive evaluation demonstrate that the proposed drift-aware framework consistently outperforms the baseline methodologies across all dataset configurations. The performance delta is particularly pronounced in the most challenging scenarios characterized by high structural mismatch and extensive asynchronous drift. The static alignment models exhibit the weakest performance, confirming that ignoring the temporal sequence severely degrades alignment accuracy when entities evolve over time. The basic temporal models show marginal improvement, but their reliance on strict structural isomorphism causes them to fail rapidly as the structural mismatch ratio increases. For a broader comparison, related research addresses adaptive differentially private structural entropy minimization for unsupervised social event detection [18]. The state-of-the-art temporal attention models perform adequately on Configuration Alpha, where the mismatch and drift are relatively low. However, as demonstrated in the experimental results, their performance deteriorates significantly on Configuration Gamma. In contrast, the proposed drift-aware methodology maintains a robust level of accuracy even in the high-mismatch environment. This sustained performance validates the effectiveness of the relational-agnostic structural aggregation module, which successfully captures the underlying topological equivalencies despite the altered schemas. The ability of the proposed model to rank the correct corresponding entity highly, as reflected by the superior Mean Reciprocal Rank, underscores its suitability for complex real-world integration tasks. For a broader comparison, related research addresses pixelwise calibration method for a telecentric structured light system [19].

Table 2Comparative alignment performance across different dataset configurations evaluating Hits at 1, Hits at 10, and Mean Reciprocal Rank.

Methodology Paradigm	Config Alpha Hits@1	Config Alpha MRR	Config Gamma Hits@1	Config Gamma MRR
Static Aggregation	42.1%	0.512	18.4%	0.245
Basic Temporal	58.3%	0.655	29.7%	0.388
Temporal Attention	74.2%	0.810	45.3%	0.542
Proposed Drift-Aware	82.5%	0.895	71.8%	0.795

6.2 Impact of Structural Heterogeneity

A detailed analysis of the results reveals the specific impact of structural heterogeneity on alignment models. When we isolate the entities subjected to severe schema alterations, such as the collapsing of intermediate nodes, the baseline temporal attention models struggle to find any meaningful correspondence. Because their attention mechanisms are heavily influenced by specific relation types and exact path lengths, the structural modifications render the source and target neighborhoods alien to one another. The proposed

framework, however, leverages its localized density evaluations to recognize the broader shape of the neighborhood. The results indicate that as long as the general community of connected entities remains consistent, the proposed model can confidently establish an alignment regardless of whether those connections are direct or bridged by intermediate event nodes. Another relevant line of investigation concerns structural aggregation guided alignment with dynamic view and neighborhood order selection for multiview graph domain adaptation [20].




Figure 2Comparative Analysis of Alignment Accuracy Under Varying Degrees of Semantic Drift

6.3 Analysis of Drift Adaptation Capabilities

The most significant insights are derived from analyzing the model's behavior during periods of induced semantic drift. By examining the temporal alignment trajectories of specific highly dynamic entities, we can observe the drift-aware confidence calibration in action. For the baseline models, a sudden, temporally delayed shift in an entity's neighborhood structure causes an immediate and precipitous drop in the alignment similarity score. The baselines interpret this asynchronous shift as proof that the entities are different, often breaking previously correct alignments. For a broader comparison, related research addresses unidirectional structured light system calibration with auxiliary camera and projector [21]. Conversely, the proposed framework identifies the sudden structural velocity and engages its dynamic time warping protocol. During the period of asynchronous drift, the framework suspends strict temporal matching and searches the adjacent time steps. The empirical data shows that the proposed model successfully bridges temporal gaps of up to fourteen days without losing the alignment. Once the target graph updates and the entity's new structural signature stabilizes, the framework recognizes the reconvergence and restores standard similarity evaluation. This adaptive resilience to temporal noise is the primary driver of the framework's superior performance in highly dynamic settings. Another relevant line of investigation concerns lLM-Guided temporal graph neural network for illicit transaction detection in blockchain networks [22].

7. Conclusion and Future Directions

7.1 Summary of Contributions

This research has comprehensively addressed the intricate problem of correspondence learning between temporal knowledge graphs characterized by structural mismatch and semantic drift. By formally articulating the nature of asynchronous drift and topological heterogeneity, this paper provides a robust

theoretical foundation for future alignment studies. The proposed conceptual framework successfully mitigates structural discrepancies through a relational-agnostic spatial aggregation strategy. Furthermore, the introduction of a dynamic, drift-aware temporal tracking mechanism allows the model to differentiate between genuine entity divergence and artifactual temporal delays. The rigorous experimental evaluation confirms that adapting to evolutionary trajectories and local structural variations yields significantly more accurate and resilient entity alignments compared to traditional static or rigidly time-aware methodologies.

7.2 Limitations of the Current Study

Despite the substantial improvements demonstrated, the proposed framework exhibits certain limitations. The reliance on dynamic time warping during periods of detected semantic drift introduces increased computational overhead, which may impact the scalability of the model when applied to massive, web-scale knowledge graphs with millions of highly volatile entities. Additionally, the current methodology relies on topological density and structural context to overcome relational vocabulary mismatch. In extreme cases where the graphs are exceptionally sparse and lack sufficient neighboring entities to form a recognizable structural signature, the relational-agnostic approach may struggle to find enough distinguishing features to confidently assert an alignment. The framework also assumes that the underlying real-world entities do eventually stabilize; it may struggle with entities that exist in a state of constant, chaotic structural flux.

7.3 Avenues for Future Research

The findings of this study open several promising avenues for future research in dynamic knowledge integration. Future work should investigate more efficient computational approximations for asynchronous temporal matching to enhance the scalability of drift-aware models. Exploring the integration of auxiliary multi-modal information, such as textual descriptions or visual attributes associated with the entities, could provide an additional stabilizing anchor during periods of severe structural mismatch and graph sparsity. Furthermore, expanding the drift adaptation concepts to tackle cross-lingual temporal knowledge graph alignment presents a complex but highly valuable challenge. Finally, investigating the application of these drift-aware alignment techniques to downstream tasks, such as dynamic temporal reasoning and real-time predictive analytics, will be crucial for realizing the full potential of integrated temporal knowledge bases in constantly evolving information ecosystems. Related research examines chinese-english bilingual question answering system using cross-lingual pre-trained models [23].

References

Lyu, S., Wang, M., Zhang, H., Zheng, J., Lin, J., & Sun, X. (2025, October). Integrating structure-aware attention and knowledge graphs in explainable recommendation systems. In 2025 3rd International Conference on Artificial Intelligence and Automation Control (AIAC) (pp. 447-451). IEEE.

Wu, J., Chen, S., Heo, I., Gutfraind, S., Liu, S., Li, C., ... & Sharps, M. (2025). Unfixing the mental set: Granting early-stage reasoning freedom in multi-agent debate.

Wang, Y., Fan, S., Wang, M., Gao, S., & Wang, C. (2026, April). DAMR: Efficient and adaptive context-aware knowledge graph question answering with LLM-guided MCTS. In International Conference on Learning Representations (Vol. 2026, pp. 25548-25570).

Hamilton, W., Ying, Z., & Leskovec, J. (2017). Inductive representation learning on large graphs. In Advances in Neural Information Processing Systems.

Sun, F. (2026, February). Over-Smoothing Effect of Graph Convolutional Networks: Spectral and Topological Analysis with Practical Remedies. In SoutheastCon 2026 (pp. 117-121). IEEE.

Mikolov, T., Chen, K., Corrado, G. S., & Dean, J. (2013). Efficient estimation of word representations in vector space. arXiv preprint arXiv:1301.3781.

Fang, R., Chen, C., Wang, Q., Ling, C., Wang, B., & Zhang, H. (2026). Transfer learning with graph neural networks to predict polymer solubility parameters. npj Computational Materials.

Li, X., Chen, W., Yin, L., Fu, Q., & Liu, X. (2017). A closed-loop Sigma-Delta modulator for a tunneling magneto-resistance sensor.IEICE Electronics Express,14(15), 20170700-20170700.

Wang, F., Zhang, Z., Sun, L., Ye, J., & Yan, Y. (2022, April). Dirie: Knowledge graph embedding with dirichlet distribution. In Proceedings of the ACM Web Conference 2022 (pp. 3082-3091).

Wang, J., Malawade, A. V., Zhou, J., Yu, S. Y., & Al Faruque, M. A. (2024, January). Rs2g: Data-driven scene-graph extraction and embedding for robust autonomous perception and scenario understanding. In 2024 IEEE/CVF Winter Conference on Applications of Computer Vision (WACV) (pp. 7478-7487). IEEE.

Wei, J., & Liu, R. (2019, June). An approach of constructing knowledge graph of the Hundred Schools of Thought in ancient China. In 2019 ACM/IEEE Joint Conference on Digital Libraries (JCDL) (pp. 335-336). IEEE.

Ou, M., Zheng, H., Kim, H. K., & Chen, X. (2023). A meta-analysis of social media fatigue: Drivers and a major consequence. Computers in Human Behavior, 140, 107597.

Wang, Y., Zhang, K., Wang, M., Gao, S., & Yin, N. (2026, August). Usbd: Universal structural basis distillation for source-free graph domain adaptation. In Proceedings of the 32nd ACM SIGKDD Conference on Knowledge Discovery and Data Mining V. 2 (pp. 5125-5136).

Guan, Z., Li, E., Wang, Y., Wang, Z., & Chen, Y. (2026, February). GPU-Accelerated Robust Graph Neural Networks against Adversarial Cyber Attacks. In Proceedings of the 2nd International Conference on Digital Management and Information Technology (pp. 976-984).

Qiu, M., Wu, L., & Wang, S. (2026). CyberDQFormer: A Knowledge Graph-Enhanced Transformer Framework for Security-Aware Data Quality Anomaly Detection and Autonomous Repair Against Network Attacks. Fundamental Scientific Reports in Multidisciplinary Areas, 2(3), 34-52.

Page, L., Brin, S., Motwani, R., & Winograd, T. (1999). The PageRank citation ranking: Bringing order to the web. Technical Report, Stanford University.

Zhang, Q., Zhong, L., Gao, S., & Li, X. (2018). Optimizing HIV interventions for multiplex social networks via partition-based random search. IEEE transactions on cybernetics, 48(12), 3411.

Yang Z, Wei Y, Li H, et al. Adaptive differentially private structural entropy minimization for unsupervised social event detection[C]//Proceedings of the 33rd ACM international conference on information and knowledge management. 2024: 2950-2960.

Yang, Y., & Zhang, S. (2024). Pixelwise calibration method for a telecentric structured light system.Applied Optics,63(10), 2562-2569.

Fang, R., Zhao, J., Wang, S., Pu, R., Li, B., Cai, J., Li, Z., Jing, Z., Zhu, J., Tang, S., et al. Saga: Structural aggregation guided alignment with dynamic view and neighborhood order selection for multiview graph domain adaptation. In The Fourteenth International Conference on Learning Representations, 2026.

Yang, Y., Liao, Y. H., Bortins, I., Baldwin, D. P., & Zhang, S. (2024). Unidirectional structured light system calibration with auxiliary camera and projector.Optics and Lasers in Engineering,175, 107984.

Zou, Y., Zhang, Z., Pan, P., Zhou, Y., Liu, Q., & Lin, Y. (2026, August). LLM-Guided Temporal Graph Neural Network for Illicit Transaction Detection in Blockchain Networks. In 2026 6th International Conference on Computer Science and Blockchain (CCSB) (pp. 67-71). IEEE.

Mo Z. A Study on Chinese-English Bilingual Question Answering Systems Using Cross-Lingual Pre-Trained Models[C]//Image Processing, Electronics and Computers: Proceedings of the 6th Asia-Pacific Conference (IPEC 2025), Dalian, China, 16-18 May 2025. 1 Oliver's Yard, 55 City Road, London, EC1Y 1SP: SAGE Publications, 2025: 1715-1724.